



## Declaration of Performance

67350040

305/2011/EU Construction Products Regulation

<b>1. Unique identification code of the product-type</b>	ISPOFLEX 40
<b>2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4).</b>	Printed on packaging
<b>3. Intended use or uses of the construction product, in accordance with the applicable harmonized technic specification, as foreseen by the manufacturer</b>	SEALANT FOR FAÇADE ELEMENTS : EN-15651-1: F-EXT-INT-CC
<b>4. Manufacturer</b>	ISPO France 3, rue de Bitschhoffen 67350 LA WALCK France
<b>5. Authorized representative</b>	Not Relevant
<b>6. Systems of assessment of performance</b>	SYSTEM 3 ; SYSTEM 3 FOR REACTION TO FIRE
<b>7. Harmonized standard</b>	EN 15651-1
<b>8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued</b>	Not Relevant

**CONDITIONING: PROCEDURE B (ACCORDING TO ISO 8340)**

**SUBSTRATE: ALUMINUM , MORTAR M2**

9. Declared Performance			
9	Essential Characteristic	Declared Performance	Harmonised Standard
9.1	Reaction to fire	Class E	
9.2	Release of Chemicals	NPD	See product safety data sheet
9.3	Water Tightness & Air Tightness as determined by :		
9.3.1	Resistance to flow	0 mm	EN 15651-1

<b>9.3.2</b>	Loss of volume	≤ 5 %	EN 15651-1
<b>9.3.3</b>	Tensile properties, i.e Elongation after immersion in water at 23 °C	Pass	EN 15651-1
<b>9.3.4</b>	Adhesion/Cohesion at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)	NF	EN 15651-1
<b>9.3.5</b>	Adhesion/Cohesion properties after exposure to heat (70°C)	NPD	EN 15651-1
<b>9.3.6</b>	Elastic recovery	≥ 70%	EN 15651-1
<b>9.3.7</b>	Durability	Pass	EN 15651-1

**10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Note: this certificate is issued electronically and is valid without signature.

ISPO France  
Thomas MENDLER  
Manager

**Disclaimer :** The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, ISPO France gives no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.